

OZONE REACTION FILTERS

HO₃

The water treatment in swimming pools has significantly changed over the past years due to the development of new technologies, ozone treatment is one of them. To preserve the hygienic conditions and comfort of a swimming pool, it is needed a proper water treatment system.



This filter is designed for the following maximum concentrations:

- OZONE : 2 PPM
- AMMONIA : 2%
- HYDROCHLORIC ACID : 5%
- SULFURIC ACID : 20%
- CHLORINE GAS : 1 PPM
- SODIUM HYPOCHLORITE : 2%
- NITRIC ACID : 0%

Can be customized by volume

Specification and size:

Model	Tank Dia	Connection Size	Height	Volume	Model	Tank Dia	Connection Size	Height	Volume
	(mm)		(mm)	(L)		(mm)		(mm)	(L)
HO ₃ -600	600	DN40	1300	0.32	HO ₃ -1200	1200	DN50	2000	2.1
HO ₃ -800	800	DN50	1500	0.63	HO ₃ -1400	1400	DN100	1600	2.1
HO ₃ -800	800	DN50	2000	0.88	HO ₃ -1600	1600	DN100	1700	2.9
HO ₃ -900	900	DN50	1500	0.81	HO ₃ -1800	1800	DN150	1850	4.0
HO ₃ -900	900	DN50	2000	1.05	HO ₃ -2000	2000	DN150	2000	5.34
HO ₃ -1000	1000	DN50	1500	1.12	HO ₃ -2300	2300	DN200	2300	7.7
HO ₃ -1000	1000	DN50	2000	1.51	HO ₃ -2500	2500	DN200	2500	10.43
HO ₃ -1200	1200	DN50	1500	1.53					