

COMMERCIAL SAND FILTERS

Q

Maximum working pressure:
2.5kg/cm²(35psi)
Maximum temperature: 45°C
Filters with special height
available by special order.



- Anti - UV protective layer of fiber glass wound reinforced filter tank.
- Integral structural polyester fiberglass bases for superior tank support.
- Fully pressure tested at the factory.
- Metric or imperial piping flanges available.
- Vertical design consumes small space footprint.
- Suitable for any filter media.
- Wide variety of sizes available.



Three-dimensional nameplate

Specification and size:

Model	Tank Dia	Connection Size	Filter Area	Flow	Silica Sand	Weight	Height
	(mm)		(m ²)	(m ³ /h)	(kg)	(kg)	(mm)
Q1200(L)	1200	DN80	1.13	56.0	1050	140	1400
Q1400	1400	DN100	1.54	78.0	1700	160	1600
Q1600	1600	DN100	2.00	102.0	2600	220	1750
Q1800	1800	DN150	2.54	126.0	3250	350	1950
Q2000	2000	DN150	3.14	159.0	4450	415	2140
Q2350	2350	DN200	4.34	201.0	6800	580	2350
Q2500	2500	DN200	4.90	235.0	8200	745	2450
Q3000	3000	DN200	7.07	350.0	11900	1050	2650