



TOP MOUNT SAND FILTERS





Maximum working pressure:
2.5kg/cm²(35psi)
Maximum temperature: 45°C
Working pressure of 4kg/cm²
available by special order.



- Tank body has twin heavy duty anti-UV polyurethane protective layer.
- Ergonomically designed six position multiport valve.
- Chemical resistance.
- Pressure gauge for inspection of operating pressure.
- Virtually maintenance free, simply backwash filter when required.
- Sand drain plug for easier sand removal-replacement.



Three-dimensional nameplate

Specification and size:

Model	Tank Dia	Connection Size	Filter Area	Flow	Silica Sand	Height	Weight	Matching multi-function valve
	(mm)		(m ²)	(m ³ /h)	(kg)	(mm)	(kg)	
Q400	400	DN40	0.13	6.3	30	750	10.3	1.5"Clamp/screw
Q450	450	DN40	0.16	8.0	45	810	12.2	1.5"Clamp/screw
Q500	500	DN40	0.22	11.5	80	870	13.7	1.5"Clamp/screw
Q650	630	DN40	0.33	16.5	130	960	18.4	1.5"Clamp/screw
Q700	700	DN40	0.38	19.2	190	1025	22.6	1.5"Clamp/screw
Q800	800	DN50	0.50	25.2	260	1130	27.7	2"screw
Q900	900	DN50	0.64	30.0	400	1270	34.5	2"screw
Q1000	1000	DN50	0.79	34.0	600	1340	46.0	2"screw
Q1100	1100	DN50	0.95	38.0	800	1460	50.5	2"screw
Q1200	1200	DN50	1.13	42.0	900	1540	62.0	2"screw
Q1400	1400	DN50	1.54	48.0	1600	1750	73.0	2"screw