

AQUA®  
爱克

The quality come from life  
品质源自于生活



## 余氯多功能水质监控仪

FREE CHLORINE MULTIFUNCTION CONTROL SYSTEM

双行16字液晶显示  
16 Words Double Line LCD Display

\*意大利原装进口  
\*Original imported from Italy

## 余氯多功能水质监控仪

FREE CHLORINE MULTIFUNCTION CONTROL SYSTEM

### AUT-800



Original imported from Italy, Using high quality electronic components and excellent housing material, is a pool water quality intelligent monitoring system, designed to control residential and commercial swimming pool and SPA pool water free chlorine content, PH value and temperature.

意大利原装进口，采用高品质电子元件和优良的外壳材质制造而成，是一款泳池水质智能监控系统，设计用于控制家用及商用泳池及SPA池水的余氯含量、PH值及温度。

### Feature:

PH measurement-- range: 0~14; Resolution:  $\pm 0.01$   
 CL measurement -- range: 0-200PPM;  
 Resolution:  $\pm 0.01$ ; Accuracy: 1%  
 Temperature measurement-- PT100; Range: 0~100°C;  
 Resolution: 1°C; Accuracy: 1%  
 Power input --100 ~ 240V, 50 ~ 60Hz  
 Signal Input -- external trigger (flow meter) input  
 (15 ~ 30Vac / Vdc)  
 Output --0 / 4 ~ 20mA, 4 dosing pump relay output  
 (10A, 230V)  
 Power --15W  
 Dimensions --300 (H)  $\times$  290 (W)  $\times$  143 (D)  
 Installation -- wall-mounting  
 Working environment -- Temperature: 0 ~ 40 °C;  
 Relative Humidity: 0 ~ 95% (non-condensing)  
 Weight --2.45kg  
 Housing material --ABS  
 Protection degree --IP65

### Accessories:

### 特点:

PH测量--范围: 0~14; 分辨率:  $\pm 0.01$   
 CL测量--范围: 0~200PPM; 分辨率:  $\pm 0.01$ ; 精度: 1%  
 温度测量--PT100; 范围: 0~100°C; 分辨率: 1°C; 精度: 1%  
 电源输入--100~240V, 50~60Hz  
 信号输入--外部触发(流量计)输入(15~30Vac/Vdc)  
 输出--0/4~20mA, 4个加药泵继电器输出(10A, 230V)  
 功率--15W  
 外形尺寸--300(高) $\times$ 290(宽) $\times$ 143(深)  
 安装方式--挂壁式  
 工作环境--温度: 0~40°C; 相对湿度:0~95%(无冷凝)  
 重量--2.45kg  
 外壳材质--ABS  
 防护等级--IP65

### 配件:

